

Folding Doors Installation Instructions

Natural Wovens

Please Follow These Installation Instructions


You will need a pencil, tape measure, drill, screwdriver, pliers and appropriate fasteners.

Step 1 Choose the Correct Fastener



No. 8 sheet metal screws for wood and aluminum

Included Fasteners




Self drilling hex head for aluminum



Rawl plug and sheet metal screw for concrete



Molly bolt for dry wall




Toggle bolt for lathe and plaster or drywall

Alternate Fasteners (not included)

OUTSIDE MOUNT

Step 2

Mount Brackets



wall bracket

Standard wall brackets are adjustable and should be mounted within 3" of each end of the track. Space any additional brackets supplied in even increments.


Step 3



Attach End Stop

Install 1 end stop with the 2 screws provided. Save the remaining end stop and install after Step 5.

Steps 4, 5 Install Track and Door




Install track by snapping into the C-clips of the bracket.

Slide all carrier wheels into the open end of the track and install the remaining end stop.

Step 6

Install Valance

Set the valance board on top of mounting brackets flush to the wall and fasten with screws from track up into the valance board.



Attach valance returns to the sides by joining velcro strips.

Step 7

Install Carrier Stop

Insert plastic Carrier Stop into track on the opposite side from the pull side.

INSIDE OR CEILING MOUNTS

Step 2

Install Valance First

Screw up through bottom of board into the window, soffit or ceiling. Valance may project beyond the opening.

Step 3

Mount Brackets



Use C-Clip bracket supplied for inside mounts. Mount C clip bracket under the valance. Allow a maximum of 3" of each end of the track. Space any additional brackets supplied in even increments.

Step 4



Attach End Stop

Install 1 end stop with the 2 screws provided. Save the remaining end stop and install after Step 6.

Steps 5, 6

Install Track and Door



Install track by snapping into the C-clips of the bracket.

Slide all carrier wheels into the open end of the track and install the remaining end stop.

Step 7

Install Carrier Stop

Insert plastic Carrier Stop into track on the opposite side from the pull side.